System Support Addendum

PRODUCT NAME: DEC SoftPC for VMS, Version 4.0 **SSA 32.18.02-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000 Model 110/310/410/610/612,

VAX 4000 Model 100/200/300/400/500/600

VAX 6000 Model 200/300/400/500/600

VAX 7000 Model 600 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350,
VAX 8500, VAX 8530, VAX 8550, VAX 8600,
VAX 8650, VAX 8700, VAX 8800, VAX 8810,
VAX 8820, VAX 8830, VAX 8840

VAX 9000 Model 110, VAX 9000 Model 210,
VAX 9000 Model 300 Series, VAX 9000 Model 400 Series

VAX 10000 Model 600 Series

VAX–11/750, VAX–11/780, VAX–11/785

MicroVAX: MicroVAX 2000,
MicroVAX 3100, Model 10/10E, 20/20E,30/40
MicroVAX 3100, Model 80, Model 90
MicroVAX 3300, MicroVAX 3400
MicroVAX 3500, MicroVAX 3600
MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540
VAXstation 4000 VLC
VAXstation 4000 Model 60, VAXstation 400 Model 90

VAXserver: VAXserver 3100 Model 10/10E, 20/20E,
VAXserver 3300,
VAXserver 3400, VAXserver 3500,
VAXserver 3600, VAXserver 3602,
VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200, VAXserver 4000 Model 300,
VAXserver 4000 Model 500

VAXserver 6000-210, VAXserver 6000-220,
VAXserver 6000-310, VAXserver 6000-320,
VAXserver 6000-410, VAXserver 6000-420,
VAXserver 6000-510, VAXserver 6000-520
VAXserver 6000-610, VAXserver 6000-620
VAXserver 6000-630

Processors Not Supported

VAX–11/725, VAX–11/782, MicroVAX I and II, VAXstation I and II, VAXstation 8000

Processor Restrictions

VAXstation 3520 and VAXstation 3540 are only supported with the VT terminals or remote X display. Local X display is not supported.

Memory Requirements

The SoftPC application requires a minimum working set of 2 MB. The minimum supported system memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 6 MB. However, the use of this software in conjunction with increased memory capability improves performance.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	20,000 blocks
Disk space required for use (permanent):	20,000 blocks

Disk space for typical use (10 MB emulated disk):\40,000 blocks)

digital™

July 1993
AE-PC3BC-TE

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

The software can use a local floppy disk drive with the following restrictions:

RX33 - Read/write high density. Read only low density. Note: RX33 not supported on machines with RQDX3 controllers.

RX23 - Read/write high density. Read-only low density.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No MOTIF Interface):

VMS Operating System V5.5

For Workstations Running MOTIF:

VMS Operating System V5.5 (and necessary components of VMS MOTIF 1.1 or later)

This product may run in either of the following ways:

- Stand-alone execution - running the X11 display server and the client application on the same machine.
- Remote execution - running the X11 display server and the client application on different machines.

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CD–ROM.

ORDERING INFORMATION

Software Licenses: QL-YNWAA-3*
Software Media: QA-YNWAA-H*
Software Documentation: QA-YNWAA-GZ
Software Product Services: QT-YNWA*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® IBM is a registered trademark of International Business Machines Incorporated.

™ PC/AT is a trademark of International Business Machines Incorporated.

™ The DIGITAL Logo, DEC, DEC SoftPC, MicroVAX, MOTIF, VAX, VMS, VAXserver and VAXstation are trademarks of Digital Equipment Corporation.